

## **Suzhou Standard Polymer CO., LTD.**

Building 88, No. 116 Wutaishan Road, Suzhou new district, Jiangsu, China

Tel: 86-512-63659176

STD2409033 is a RAL1026 yellow. Which can be used for films, fibers, pipes, injection.

STD2409033 can pass ROHS regulation.

STD Code: STD2409033	TECHNICAL DATA SHEET
Test	Result
Melt Temperature(°C)	125
Let Down(%)	3.0% depending on application
Heat Stability(°C)	250
Carrier	LLDPE
Resin Suitability	PE,PP,Ethylene copolymers
Water Ratio(%)	≤0.30
Migration Resistance(level)	4
Heat Resistance(level)	5
Light Fastness(level)	3-4
Main Application	Blowing,Injection,Extruction,etc

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variation in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the application disclosed.Full-scale testing and end product performance are the responsibility of the user. Suzhou Standard Polymer shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Suzhou Standard Polymer Co.,Ltd. direct control. Suzhou Standard Polymer makes no warranties, expressed or implied, but not limited to,the implied warranties of merchantability and fitness for a oarticular purpose.